

## 2025 New England SOLO/TWIN Championships REQUIRED SAFETY EQUIPMENT

## Return this completed form to the Event Organizers

The following items are required equipment based on ORC Regulations for Category 3 offshore events and must be carried during the New England SOLO/TWIN. Items on this sheet should be assembled and stowed in their proper place on board your vessel.

Entrants should be prepared to show any and all required equipment to race committee officials and demonstrate procedures for proper use should a random spot safety check of any vessel be mandated by the Race Organizers — either prior to or at any point after the race. The Event Organizers will not take it on faith that any incomplete or unchecked items will be aboard prior to the start; the entrants' signatures attest to compliance to entry requirements at the time this form is signed, dated, and relinquished to the Event Organizers.

Check off each item on the following list and sign the bottom. Signatures for BOTH double-handed entrants are required; as coskippers, both crew members are responsible for knowing what equipment is on board and its proper use. This form, completed and signed, must be submitted to the Event Organizers by no later than 2000 hours on Thursday, the day before the start. Failure to do so will disqualify entrants from starting.

so will disqualify entrants from starting.		
Each SOLO yacht must have a system for set steering devices will be allowed on TWIN yachtEach yacht must carry a VHF marine radiot 16 and 72 required for race communication mustCarrying a self-inflating liferaft is strongly not required. Each crewmember is required to he Type-One USCG-approved life jacket - fitted w attached personal overboard light and whistle. (I gear for the life raft should include an "abandon water, food, knife, flares, flashlights, extra batte etc.). Each yacht must have jack lines, running from to the foredeck, so that the crew can move from forestay without disconnecting a safety harness.  It is strongly recommended that a safety har lifejacket be worn and attached to the yacht at synthe Sailing Instructions 18.2), except when crew below decks. A harness shall be fitted with a crestraps.  Visual distress signals must include two ora and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares. Three words and three red meteor or parachute flares.  The yacht must have a system for re-boarding lines or a ladder, in place at all times.  A radar reflector must be in place at least situations.	elephone. Channels to be operational.  recommended but ave on board a ith reflective tape, NOTE: Survival ship kit" with ries, first-aid kit,  om near the cockpit the yacht's stern to ress and inflatable pecified times (see members are otch strap or thigh the yacht's stern to ange smoke signals white flares or a he yacht's	Proper sail numbers must be displayed on the mainsail. This deletes Racing Rules of Sailing paragraph G 1.3 (c) Headsails and Spinnakers.  Man-overboard pole and flag with horseshoe life ring (mandatory for TWIN). A certified Man Overboard Module (MOM) or Dan Buoy with inspection expiration date not prior to June 30 of the year of the race is an acceptable alternative. Not required for SOLO yachts.  Yachts must fly International Code Pennant from the backstay (or similar position) to indicate which class that they are participants in; 1-3 twin spin, 4 cruising non-spin, 5 solo spin, 6 multihulls  Each yacht shall carry suitable anchor(s) and cable(s) and adequate rode.  Each yacht shall carry softwood plugs of suitable size for emergency closure of through-hull fittings.  There shall be companionway blocking arrangements (washboards, hatchboards, etc.) capable of being secured in position with the hatch open or shut and secured to the yacht to prevent their being lost overboard.  Each yacht shall have an effective method of reefing the mainsail and a headsail suitable for use in heavy weather.  Each yacht should have aboard suitable charts, navigational equipment, compass, and a copy of all sailing instructions.  Each yacht is required to have working navigational lights.  Each yacht shall carry two (2) waterproof flashlights.
STATEMENT OF COMPLIANCE TO SAFETY EQUIPMENT REQUIREMENTS  The undersigned hereby acknowledge and verify that the aforementioned safety equipment is on board the vessel named below, and that said		
equipment is indeed on board, in position and operational, as of the date shown below.		
Co-Entrant's Signature	Co-Entrant's Signat	ure Yacht's Name (PLEASE PRINT)
Co-Entrant's Name (PLEASE PRINT)	Co-Entrant's Name	(PLEASE PRINT) Date of Compliance